

Product advantage

- Cat.5E unshielded module meets ANSI/TIA 568.2-D Cat.5E, ISO/IEC 11801 2nd Class D and EN50173 2nd Edition standards and passed ETL unit testing certification.
- The module is equipped with a rotary dust cover to reduce dust intrusion (IP20 rated). Modules of eight different colors can be selected according to the application requirements, which conforms to TIA-606 color management standard.
- The circuit board IDC terminal adopts the press in technology, which can effectively reduce the capacitance effect and suppress the crosstalk.
- Provide a tool free crimping cover to prevent the cable from falling off and reduce the poor contact caused by dust.
- The module has EIA color code sticker, which conforms to two wiring methods of T568A and T568B.
- 110/krone wiring tools are compatible with quick connect IDC terminal design, supporting traditional 110 wiring tools and special 4-Pair wiring tools (FL-KM90T/FL-KM18T) quick installation mode. 22-26awg cable can be terminated.
- Comply with RoHS 2011/65/EU environmental protection standards.



Product characteristics

- Shell plastic material: fire resistant ABS (in accordance with UL-94V-0)
- Contact material: copper tin plating
- Contact plating: 50 μ Gold Plated / 100 μ plate with nickel
- Interface plugging times: >1000
- IDC wiring and termination times: >200
- Plug and pull resistance: minimum 11lbf (50N) between plug and interface
- Contact pressure of plug and interface: 100 grams minimum for each contact
- Operating temperature: -40 °C to +75 °C
- Insulation strength (conductor conductor): 1000VAC, 60Hz/1min
- Insulation impedance: >500M ohms (500VDC)
- Contact impedance: <20M ohms
- Rated voltage / current: 150VAC/1.5Ampere

Meet the standards

- TIA/EIA 568-B.2 Category 5E
- ANSI/TIA 568.2-D Category 5E
- ISO/IEC 11801 2nd Edition
- EN 50173 2nd Edition
- EN 55022 Class B

Can be used

- 10/100Base-TX
- 1000Base-T
- 155/622 Mbps ATM
- TP-PMD(ANSI X3T9.5 100Mbps)
- 4/16Mbps Token Ring
- ISDN
- VoIP
- PoE

Order information

Product model	Description	Packing								
FL-51KU-XX	Cat.5E RJ45/u Keystone jack 90 degree	1pc/pk								
FL-52KU-XX	Cat.5E RJ45/u Keystone jack 180 degree	1pc/pk								
FL-KCAP-V	90 degree Keystone jack IDC block cap	50pcs/pk								
Color code-XX	<table border="1"> <tr> <td>01</td> <td>02</td> <td>03</td> <td>04</td> </tr> <tr> <td>05</td> <td>06</td> <td>07</td> <td>08</td> </tr> </table>	01	02	03	04	05	06	07	08	
01	02	03	04							
05	06	07	08							