

Product model	Description	Packing
FL-PAMB22081G-M002	OM3 MPO(female) to MPO(female) 08C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk
FL-PAMB22121G-M002	OM3 MPO(female) to MPO(female) 12C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk
FL-PACB22081G-M002	OM4 MPO(female) to MPO(female) 08C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk
FL-PACB22121G-M002	OM4 MPO(female) to MPO(female) 12C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk
FL-PATB44081G-M002	OS2 MPO/APC(female) to MPO/APC(female) 08C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk
FL-PATB44121G-M002	OS2 MPO/APC(female) to MPO/APC(female) 12C key up to key up Array cord (Type B) LSFRZH 2m	1pcs/pk

Model and coding method of Pre terminated Array cord

FL-PA	B	C	D	E	FFF	G	-	H	III
Cable Type A Array cord (round cable)	Polarity A key up to key down B key up to key up notes: FL default: Type-B		Termination End B 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female		Jacket Type E OFNR F OFNR + end B pulling eye G LSFRZH H LSFRZH + end B pulling eye X OFNP Y OFNP + end B pulling eye				Length 001-XXX
Fiber Type M MaxCap 300 OM3 50/125μm C MaxCap 550 OM4 50/125μm T TeraCap 9/125μm OS2 / G.657-A1 S TeraSafe 9/125μm ITU-T G.657-A2			Termination End A 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female		Fiber Count 081 8C Fiber x 1 121 12C Fiber x 1			Unit of Measure F Feet M Meters	