



阵列光纤跳线



产品型号	描 述	包装
FL-PAMB22081G-M002	8C 多模万兆OM3 MPO(母)-MPO(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk
FL-PAMB22121G-M002	12C 多模万兆OM3 MPO(母)-MPO(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk
FL-PACB22081G-M002	08C 多模万兆OM4 MPO(母)-MPO(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk
FL-PACB22121G-M002	12C 多模万兆OM4 MPO(母)-MPO(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk
FL-PASB44081G-M002	8C 单模OS2 MPO/APC(母)-MPO/APC(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk
FL-PASB44121G-M002	12C 单模OS2 MPO/APC(母)-MPO/APC(母) 预端接阵列光纤跳线-2米, LSFRZH	1pcs/pk

阵列光纤跳线编号规则

FL-PA	B	C	D	E	FFF	G	-	H	III
Cable Type A Array cord (round cable)	Polarity A key up to key down B key up to key up 备注: 默认采用Type- B		Termination End B 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female		Jacket Type E OFNR F OFNR + end B pulling eye G LSFRZH H LSFRZH + end B pulling eye X OFNP Y OFNP + end B pulling eye			Length 001-XXX	
Fiber Type M MaxCap 300 OM3 50/125μm C MaxCap 550 OM4 50/125μm T TeraCap 9/125μm OS2 / G.657-A1 S TeraSafe 9/125μm ITU-T G.657-A2		Termination End A 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female		Fiber Count 081 8C Fiber x 1 121 12C Fiber x 1		Unit of Measure F Feet M Meters			