



Model of Pre terminated Distribution cable



Product model	Description	Packing
FL-PDMB3312BG-M010	OM3 Break-out 12C distribution cable,A-end: LC w/clip B-end: LC w/clip, Aqua , 10m, LSFRZH	1pcs/pk
FL-PDCB3312BG-M010	OM4 Break-out 12C distribution cable,A-end: LC w/clip B-end: LC w/clip, Aqua , 10m, LSFRZH	1pcs/pk
FL-PDSB3312BG-M010	OS2 Break-out 12C distribution cable, A-end: LC w/clip B-end: LC w/clip, Yellow , 10m, LSFRZH	1pcs/pk
FL-PDMB3308BG-M010	OM3 Break-out 8C distribution cable,A-end: LC w/clip B-end: LC w/clip, Aqua , 10m, LSFRZH	1pcs/pk

Coding method of Pre terminated Distribution cable

FL	P	A	B	C	D	E	FFF	G	-	H	III
Cable Type			Polarity		Termination End B		Jacket Type				Length
D Distribution cable			A key up to key down		1 ST		E OFNR				001-XXX
			B key up to key up		2 SC		F OFNR + end B pulling eye				
					3 LC		G LSFRZH				
					4 FC		H LSFRZH + end B pulling eye				
					5 Uniboot LC		I OFNR Armored				
					6 Uniboot SC		J OFNR Armored + end B pulling eye				
Fiber Type							K LSFRZH Armored				
B BaseCap 62.5/125 µm							L LSFRZH Armored + end B pulling eye				
OM1 Multimode							X OFNP				
H HiCap 50/125 µm							Y OFNP + end B pulling eye				
OM2 Multimode											
M MaxCap Safe 300											
OM3 50/125 µm											
C MaxCap Safe 550											
OM4 50/125 µm											
T TeraSafe 9/125 µm											
OS2 / G.657.A1											
S TeraSafe Plus 9/125 µm											
ITU-T G.657.A2											