MODEL NO : TM121JDGP30

MODEL VERSION: 00

SPEC VERSION : V1.3

ISSUED DATE: 2020-4-01

■ **Preliminary Specification**

☐ **Final Product Specification**

Customer :_____

Approved by	Notes

TIANMA Confirmed :

Prepared by	Checked by	Approved by
Gang.Li	Longping.Deng	

This technical specification is subjected to change without notice

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

Table of Contents

Table of Contents....2
Record of Revision....3
1 General Specifications....4
2 Input/Output Terminals....5
3 Absolute Maximum Ratings....6
4 Electrical Characteristics....7
5 Timing Chart....10
6 Optical Characteristics....13
7 Environmental / Reliability Test....17
8 Mechanical Drawing....18
9 Packing Drawing....19
10 Precautions For Use of LCD Modules....21

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

Record of Revision

Rev	Issued Date	Description	Editor
1.0	2019-01-25	Preliminary Specification Released.	Gang.Li
1.1	2019-10-23	Update more details.	Gang.Li
1.2	2020-03-10	Update mechanical drawing(modify screw hole of short side) on page18.	Gang.Li
1.3	2020-04-01	Modify display direction on page5. Update timing on page10.	Gang.Li

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

1 General Specifications

Feature		Spec
Display Spec.	Size	12.1 inch
	Resolution	1280(RGB) x 800
	Technology Type	SFT
	Pixel Configuration	R.G.B. Vertical Stripe
	Pixel Pitch (mm)	0.204x0.204
	Display Mode	Transmissive, Normally Black
	Surface Treatment(Up Polarizer)	AG
	Viewing Direction	All direction
Mechanical Characteristics	LCM (W x H x D) (mm)	278.0x184.0x9.9
	Active Area(mm)	261.1x163.2
	With /Without TSP	Without Touch Screen
	Matching Connection Type	JAE:FI-X30CL
	Weight (g)	445
Electrical Characteristics	Interface	1port LVDS, 6/8bit selectable
	Color Depth	16.7M

Note 1: Viewing direction for best image quality is different from TFT definition, there is a 180 degree shift.

Note 2 : Requirements on Environmental Protection: Q/S0002

Note 3 : LCM weight tolerance : +/- 5%

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

2 Input/Output Terminals


2.1 TFT LCD Panel

Connector type: 093G30-B0001A-M4(Starconn) Matching Connector: JAE FI-X30CL or compatible

No	Symbol	I/O	Description	Comment
1	VLED	P	Backlight power supply +12V	
2	VLED	P	Backlight power supply +12V	
3	VLED	P	Backlight power supply +12V	
4	VLED	P	Backlight power supply +12V	
5	VLED_EN	P	Backlight on/off control (1: ON, 0:OFF)	
6	VLED_PWM	P	Backlight dimming control	
7	GND	P	Power ground	
8	GND	P	Power ground	
9	VDD	P	Power Supply +3.3V	
10	VDD	P	Power Supply +3.3V	
11	GND	P	Power ground	
12	GND	P	Power ground	
13	Rxin0-	I	-LVDS differential data input(R0~R5,G0)	
14	Rxin0+	I	+LVDS differential data input(R0~R5,G0)	
15	GND	P	Power ground	
16	Rxin1-	I	-LVDS differential data input(G1~G5,B0~B1)	
17	Rxin1+	I	+LVDS differential data input(G1~G5,B0~B1)	
18	GND	P	Power ground	
19	Rxin2-	I	-LVDS differential data input(B2~B5,HS,VS,DE)	
20	Rxin2+	I	+LVDS differential data input(B2~B5,HS,VS,DE)	
21	GND	P	Power ground	
22	RxCLK-	I	-LVDS differential data input	
23	RxCLK+	I	+LVDS differential data input	
24	GND	P	Power ground	
25	Rxin3-	I	-LVDS differential data input(R6~R7,G6~G7,B6~B7)	
26	Rxin3+	I	+LVDS differential data input(R6~R7,G6~G7,B6~B7)	
27	GND	P	Power ground	
28	SEL6/8	-	Low-->6 bit input mode High or NC-->8 bit input mode	
29	GND	P	Power ground	
30	GND	P	Power ground	

Note1: I/O definition: I-----Input P----Power/Ground

Note2: Display direction (PCB at down side)





The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

3 Absolute Maximum Ratings

3.1 Driving TFT LCD Panel

GND=0V

Item	Symbol	MIN	MAX	Unit	Remark
Voltage Input	Vin	-0.50	5.00	V	Note1
Operating Temperature	T_{op}	-20.0	70.0	℃	
Storage Temperature	T_{st}	-30.0	80.0	℃	
Relative Humidity (Note2)	RH	--	≤95	%	Ta≤40℃
		--	≤85	%	40℃＜Ta≤50℃
		--	≤55	%	50℃＜Ta≤60℃
		--	≤36	%	60℃＜Ta≤70℃
		--	≤24	%	70℃＜Ta≤80℃
Absolute Humidity	AH	--	≤70	g/m^3	Ta＞70℃

Table 3.1 absolute maximum rating

Note1: Input voltage include Rxin0-/+, Rxin1-/+, Rxin2-/+, Rxin3-/+, RxCLK-/+, PWM,EN,VDD.

Note2: Ta means the ambient temperature.
It is necessary to limit the relative humidity to the specified temperature range.
Condensation on the module is not allowed.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

4 Electrical Characteristics

4.1 Driving TFT LCD Panel

VCC=3.3V,GND=0V, Ta=25℃

Item		Symbol	MIN	TYP	MAX	Unit	Remark
Power supply Voltage		VDD	3.00	3.30	3.60	V	
Power supply ripple		Vp-p	-	-	100	mV	
Power supply current		IDD	-	255	-	mA	
Power consumption		P	-	842	-	mW	Note1
Differential input voltage		|Vid|	200	-	600	mV	
Differential input common voltage		V_{CM}	-	1.2	-	V	
Differential input threshold voltage	Low level	VTL	-100	-	-	mV	
	High level	VTH	-	-	100	mV	
Inrush current		Irush	-	-	1.5	A	Note2

Table 4.1 LCD module electrical characteristics





Figure4.1 LVDS characteristics

Note1: To test the current dissipation, using the “white pattern” shown.



Note2: Inrush current definition.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

4.2 Driving Backlight

Ta=25℃

Item		Symbol	Min	Typ	Max	Unit	Remark
Backlight power supply voltage		VLED	10	12	15	V	
Backlight power supply current		I_LED	-	800	-	mA	
Backlight power consumption		P_LED	-	9600	-	mW	
Input voltage for VLED_PWM signal	High level		-	2.0	-	5.0	V	
	Low level		-	0	-	0.4	V	
Input voltage for VLED_EN	High level		-	2.0	-	5.0	V	
	Low level		-	0	-	0.4	V	
VLED_PWM frequency		Fpwm	200	-	20K	HZ	
VLED_PWM duty		D	1	-	100	%	Note1
Operating Life Time		--	50000	-	--	hrs	Note2
Inrush current		I_R	-	-	1.5	A	Rising time:470us

Note 1: According to LED driver IC characteristics, the minimum value of VELD_PWM duty may vary with VLED_PWM frequency, higher the frequency, bigger the duty.


Note 2: Optical performance should be evaluated at Ta=25℃ only.

Note 3: If LED is driven by high current, high ambient temperature & humidity condition. The life time of LED will be reduced.

Note 4: Operating life means brightness goes down to 50% of initial brightness. Typical operating life time is estimated data.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

4.3 Block Diagram



Note1: Relations between GND (Signal ground and LED driver ground) and FG (Frame ground) in the LCD module are as follows:

GND - FG	Connected

Note2: GND and FG must be connected to customer equipment's ground, and it is recommended that these grounds be connected together in customer equipment.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

5 Timing Chart

5.1 LVDS signal timing characteristics

VCC=3.3V, GND=0V, Ta=25℃

Parameter	Symbol	Value			Unit	Note
		min	typ	max		
CLK frequency	t_{clk}	-	72.2	-	Mhz	
Horizontal blanking time	t_{HBT}	-	156	-	t_{clk}	$t_{hbp} + t_{HFP}$
Horizontal black porch	t_{HBP}		84		t_{clk}	
Horizontal display area	t_{HD}		1280		t_{clk}	
Horizontal front porch	t_{HFP}	-	72	-	t_{clk}	
Horizontal period	t_H	-	1436	-	t_{clk}	
Horizontal pulse width	t_{HPW}	-	4	-	t_{clk}	
Vertical blanking time	t_{VBT}	-	38	-	t_H	$t_{VBP} + t_{VFP}$
Vertical black porch	t_{VBP}		23		t_H	
Vertical display area	t_{VD}		800		t_H	
Vertical front porch	t_{VFP}	-	15	-	t_H	
Vertical period	t_V	-	838	-	t_H	
Vertical pulse width	t_{VPW}	-	4	-	t_H	

Table 5.1 timing parameter

5.2 Input Clock and Data timing Diagram:




Figure 5.2 Input signal data timing

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

5.3 LVDS data input format




Figure 5.3 LVDS data input format (VESA standard)

Note: This LCD module supports SYNC-DE mode only, so HSYNC&VSYNC signal is necessary.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

5.4 Power On/Off Sequence

Item	Symbol	Min	Typ	Max	Unit	Remark
VDD on to VDD stable	Tp1	0.5	-	10	ms	
VDD stable to signal on	Tp2	0	-	50	ms	
Signal on to VLED_EN on	Tp3	200	-	-	ms	
PWM on to VLED_EN on	Tp4	0	-	200	ms	
VLED to PWM on	Tp5	10	-	-	ms	
VLED on to VELD stable	Tp6	0.5	-	10	ms	
VDD off time	Tp7	0	-	10	ms	
VDD off to next VDD on	Tp8	500	-	-	ms	
Signal off before VDD off	Tp9	0	-	50	ms	
VLED_EN off before signal off	Tp10	200	-	-	ms	
VLED_EN off before PWM off	Tp11	0	-	200	ms	
PWM off before VLED off	Tp12	10	-	-	ms	

Table 5.4 Power on/off sequence




Figure 5.4 Interface power on/off sequence

Note: It is advised that backlight turned on later than display stabled.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

6 Optical Characteristics

6.1 Optical Specification

Ta=25℃

Item		Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles		θT	CR≧10	75	85	-	Degree	Note 2
		θB		75	85	-		
		θL		75	85	-		
		θR		75	85	-		
Contrast Ratio		CR	θ=0°	800	1000	-	-	Note1 Note3
Response Time		T_{ON}	25℃	-	16	-	ms	Note1 Note4
		T_{OFF}		-	16	-		
Chromaticity	White	x	Backlight is on	0.25	0.3	0.35	-	Note5 Note1
		y		0.27	0.32	0.37		
	Red	x		0.593	0.643	0.693		
		y		0.286	0.336	0.386		
	Green	x		0.253	0.303	0.353		
		y		0.571	0.621	0.671		
	Blue	x		0.096	0.146	0.196		
		y		0.032	0.082	0.132		
Uniformity		U	-	70	75	-	%	Note1 Note6
NTSC		-	-	67	72	-	%	Note 5
Luminance		L	-	360	450	-	cd/m^2	Note1 Note7


Test Conditions:

1. The ambient temperature is 25±2℃.humidity is 65±7%
2. The test systems refer to Note 1 and Note 2.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Note 2: Definition of viewing angle range and measurement system.

viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80)。




Fig. 1 Definition of viewing angle

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$


“White state “:The state is that the LCD should driven by Vwhite.

“Black state”: The state is that the LCD should driven by Vblack.

Vwhite: To be determined Vblack: To be determined.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (TON) is the time between photo detector output intensity changed from 90% to 10%. And fall time (TOFF) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

Luminance Uniformity(U) = Lmin/ Lmax

L-------Active area length W----- Active area width




Fig. 2 Definition of uniformity

Lmax: The measured maximum luminance of all measurement position.

Lmin: The measured minimum luminance of all measurement position.

Note 7: Definition of Luminance :

Measure the luminance of white state at center point.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.


7 Environmental / Reliability Test

No	Test Item	Condition	Remark
1	High Temperature Operation	Ta=+70℃, 240hrs	(Note1) IEC60068-2-1:2007,GB2423.2-2008
2	Low Temperature Operation	Ta=-20℃, 240hrs	IEC60068-2-1:2007 GB2423.1-2008
3	High Temperature Storage (non-operation)	Ta=+80℃, 240hrs	IEC60068-2-1:2007 GB2423.2-2008
4	Low Temperature Storage (non-operation)	Ta=-30℃, 240hrs	IEC60068-2-1:2007 GB2423.1-2008
5	High Temperature & High Humidity Operation	Ta = +60℃, 90% RH max,240 hours	(Note2) IEC60068-2-78 :2001 GB/T2423.3—2006
6	Thermal Shock (non-operation)	-30℃ 30 min~+80℃ 30 min, Change time:5min,100cycles	Start with cold temperature, End with high temperature, IEC60068-2-14:1984,GB2423.22-2002
7	Electro Static Discharge (operation)	C=150pF,R=330Ω; Contact:±4Kv, 5times; Air:±8KV,5times;	IEC61000-4-2:2001 GB/T17626.2-2006
8	Vibration (non-operation)	Frequency range:10 ～ 55Hz, Stroke:1.5mm Sweep:10Hz ～ 55Hz ～ 10Hz 2hours for each direction of X.Y.Z (6 hours total)	IEC60068-2-6:1982 GB/T2423.10—1995
9	Shock (non-operation)	60G 6ms, ±X,±Y,±Z 3 times for each direction	IEC60068-2-27:1987 GB/T2423.5—1995
10	Package Drop Test	Height:80 cm,1 corner, 3 edges, 6 surfaces	GB/T4857.5—1992
11	Package Vibration	Frequency：5-20-200HZ， PSD：0.01-0.01-0.001 Total：0.781g2/HZ, （x/y/z each direction 30min）	GB/T4857.23-2012

Note1: Ta is the ambient temperature of sample.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

8 Mechanical Drawing




The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

9 Packing Drawing

No	Item	Model (Material)	Dimensions(mm)	Unit Weight(Kg)	Quantity	Remark
1	LCM module	TM121JDGP30-00	278.0x184.0x9.9	0.445	15	
2	Carton	CORRUGATED PAPER	530×430×274	1.06	1	
3	Dust-proof Bag	PE	700×530×0.08	0.06	1	
4	Label	Label	100×52	0.000345	1	
5	EPE	EPE	395.0×249.0×5.0	0.0115	1	
6	Corrugated Bar	Corrugated paper	379.0×300.0	0.1	1	
7	Partition_1	CORRUGATED PAPER	513.0×295.0×240	1.77	1	
8	Partition_2	CORRUGATED PAPER	513.0×413.0×7	0.142	1	
9	Anti-static Bag	PE	300.0×250	0.0106	15	
10	Total weight(Kg)	9.97Kg±5%				


The packing method is shown as below:

1. Module in air bag.




The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.


2. Dummy packing.



3. Module in carton.



4. Seal.



5. Carton on pallet



Note: 2x2x5

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.

10 Precautions For Use of LCD Modules

10.1 Handling Precautions

10.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

10.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

10.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

10.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

10.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

10.1.6 Do not attempt to disassemble the LCD Module.

10.1.7 If the logic circuit power is off, do not apply the input signals.

10.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

10.1.8.1 Be sure to ground the body when handling the LCD Modules.

10.1.8.2 Tools required for assembly, such as soldering irons, must be properly ground.

10.1.8.3 To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

10.1.8.4 The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

10.2 Storage Precautions

10.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

10.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ～ 40℃ Relatively humidity: ≤80%

10.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

10.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

The information contained herein is the exclusive property of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of SHANGHAI TIANMA MICRO-ELECTRONICS Corporation.