
The super wall paint system 2008北京奥运环境建设指定生产企业





® SUPER QUALITY | This product is using the latest PALACE paint technology, the advantages of the traditional performance of coatings and a paint set. At the same time, integration of "clean flavor," "In addition to formaldehyde," and so on paint the world's leading scientific and technological achievements to create a fresh and clean with you, Healthy home environmental protection





GREEN ENVIRONMENTAL PROTECTION

本企业通过ISO9001-2000国际质量体系认证



2008北京奥运环境建设指定生产企业





® SUPER QUALITY | This product is using the latest PALACE paint technology, the advantages of the traditional performance of coatings and a paint set. At the same time, integration of "clean flavor," 'In addition to formaldehyde," and so on paint the world's leading scientific and technological achievements to create a fresh and clean with you, Healthy home environmental protection

全国统一免费服务热线: 4000-222-886

本产品采用现代最新技术,精选各进口原料。以采用耐风化,耐酸雨,气密性强 的高效合成树脂, 配以耐紫外线的颜料组成, 并起保护建筑墙面, 延长建筑物的 使用寿命和环保、装饰的三重效果。

- 1、漆膜坚韧耐久,光滑细腻,色调高雅柔和,遮盖力强,保色性忧。
- 2、耐水、耐擦洗、耐沾污、防霉抗碱,易清洁,施工简便。
- 3、无毒无味、不燃、无有毒气体释放,是一种高品质的环保型墙体涂装系统。
- 4、用于各类建筑之水泥砂浆、灰浆、石膏板、三合板等表面,也适用于浴室、

施工注意事项

- 1、喷涂、辊涂、刷涂均可
- 2、使用前请充分搅拌均匀,可用清水稀释到流平度(约20%左右)
- 3、施工表面必须平实、无油污、新造墙面应充分干透后方可施工。
- 4、涂漆前底材表面应用腻子进行满批,干后打磨平整光滑,油漆表面效果的好坏,取决 于漆膜下物件表面的平滑程度。

- 5、一般应涂刷二至三遍,每道间隔不少于两小时,实干在48小时以上完全成膜时
- 6、根据不同型号的漆油,涂刷面积(两道),每公斤约4-10平方米。
- 7、温度低于6摄氏度,湿度大于85%,不宜施工。
- 8、贮存于阴凉干燥处,温度不得低于0摄氏度以下,或高于45摄氏度以上。保存 期限一年(原容器正常密封情况下)

亚洲总代理:

有利华国际(香港)公司 地址:香港九龙尖沙咀梳士巴利道3号 厦门市闽粤涂料工业有限公司 星光行大厦822号 传真: 00852-24299280



地址:厦门市杏林台商投资区杏美路7号 网址: www.bltuliao.com

