



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to DIN 72594-1

Documents

Assembly instruction MA_59V010

Material and plating

Connector parts

- Center contact
- Outer contact
- Dielectric
- Crimping ferrule

Material

- Brass
- Brass
- PTFE
- Copper

Plating

- Gold, min. 0.8 µm, over chemical nickel
- Nickel 2.5-5 µm
- Nickel 2.5-5 µm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05:10/6.0

FAKRA -
HF

STRAIGHT PLUG

59S17E-102A4

Electrical data

Impedance	50 Ω *
Frequency	DC to 1 GHz
Return loss	≥ N/A
Insertion loss	≤ 0.1 x √f(GHz) dB
Insulation resistance	≥ 1x10 ³ MΩ
Center contact resistance	≤ 5 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Power current	≤ 1 A DC
RF-leakage	≥ 65 dB up to 1 GHz

- Limitations are possible due to the used cable type - * Interface only

Mechanical data

Mating cycles	≥ 25
Engagement force	≤ 25 N
Disengagement force	≥ 2 N

Environmental data

Temperature range	-40°C to +85°C / 105°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
RoHS	compliant

- Limitations are possible due to the used cable type -

Tooling

Crimping tool	11W150-000 d
Crimp insert	11W15A-502

Suitable cables

Cable type	RG 179
------------	--------

Packing

Standard	1000 pcs in box, 3000 pcs in reusable container
Weight	2.0g/pce

Change History

Rev.	Date	Change
d00	11/09/13	Tooling changed: - from Crimping tool 11W15A-000 to 11W150-000

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
D. Oberhöller	11.10.05	W. Lankes	11.09.13	d00	13-1025	M. Kotewitz	11.09.13

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de			Page 2 / 2
--------------------------------------------------------------------------------------------------------------------------------------------------------	--	--	--	-----------------------------------------------------------------------------------------------------------------------	--	--	---------------