



S+S REGELTECHNIK



RCO2-AS NT
with acoustic signal
and plug-in power supply unit
for direct wall mounting



RCO2-AS NT ST
with acoustic signal,
plug-in power supply unit
and stainless steel stand
as desktop device

- AERASGARD® **RCO2-AS NT**
- AERASGARD® **RCO2-AS NT ST**
- AERASGARD® **RCO2-AS UPNT**

MAINTENANCE-FREE **CO2 SENSOR** DEVICES WITH
POWER SUPPLY UNIT FOR ANTI-INFECTION VENTILATION
IN MEDICAL PRACTICES, WAITING ROOMS,
BEAUTY SALONS, ETC.



PRODUCT RANGE 2021

CO2 Traffic Light

SIGNALS THE CURRENT VENTILATION DEMAND AT A GLANCE

For in-wall mounting
by a qualified technician:
RCO2-AS UPNT
with in-wall power supply unit



- LED 1, green:** no action required
- LED 2, green:** prompt airing recommended
- LED 3, yellow:** airing recommended
- LED 4, yellow:** airing required
- LED 5, red:** intensive airing necessary



A lot of breathing occurs where people meet in rooms. Next to the CO₂ concentration in the room air, this also increases the number of aerosols which can carry pathogens, such as the coronavirus. The CO₂ load is therefore considered an indicator for effective anti-infection protection by timely intermittent ventilation. This enables energy efficient on-demand room ventilation, thus reducing operating costs and increasing the well-being of occupants.

To this end we have extended the range of our proven **AERASGARD®** CO₂ room measuring devices with the following versions: **RCO2-AS NT ST** as plug-and-play desktop device with stainless steel stand, **RCO2-AS NT** for direct wall mounting with plug-in power supply unit, and **RCO2-AS UPNT** for installation on flush mounting sockets.

The CO₂ content is measured by means of an optical sensor using non-dispersive infrared technology (NDIR). The result is immediately indicated by five traffic light colour LEDs. In addition, a signal tone sounds when the next warning level is reached (can be deactivated per DIP switch). The devices are maintenance-free and self-calibrating. One sensor for every 30m² of room area is recommended.

AERASGARD® RCO2-AS xx					
Room CO ₂ sensor with traffic light display and acoustic signal					
Type / WG02	Measuring ranges CO ₂	Display CO ₂	Equipment	Item no. (Baldur 1)	Price
RCO2-AS xx					
RCO2-AS	0...3000ppm	5 LEDs, signal tone	without power supply unit	1501-61A0-0686-230	187,25 €
RCO2-AS NT ST	0...3000ppm	5 LEDs, signal tone	Micro-USB power supply unit, stainless steel stand	1501-61A0-0686-231	198,75 €
RCO2-AS NT	0...3000ppm	5 LEDs, signal tone	Plug-in power supply unit	1501-61A0-0686-232	191,25 €
RCO2-AS UPNT	0...3000ppm	5 LEDs, signal tone	In-wall power supply unit	1501-61A0-0686-233	279,16 €

* Installation and connection of the flush-mount power supply unit must be performed by a qualified technician!

You can find technical data and further information in our web shop or catalogue.

S+S REGELTECHNIK GMBH
THURN-UND-TAXIS-STR. 22
90411 NUREMBERG / GERMANY

FON +49 (0) 911 / 5 19 47-0
FAX +49 (0) 911 / 5 19 47-70
FAX +49 (0) 911 / 5 19 47-73

mail@SplusS.de
www.SplusS.de



Qualitätsmanagementsystem
ISO 9001

- Kundenorientierung
- Kundenzufriedenheit
- Fortlaufende Verbesserung
- System- bzw. Prozesswirksamkeit

ID 15 100 21333

www.tuev-thueringen.de

Our development and production in Nuremberg, Germany, is certified by the Technical Inspection Authority (TÜV) in Thuringia to DIN EN ISO 9001:2015.



DIN tested and certified



RoHS tested and certified



ESD compliant manufacturing



EAC certified



GOST certificates for export of all S+S products to CIS member states



CE compliant devices tested by external laboratories

Prices by S+S are understood plus legal value added tax at the respective rate in effect. All information provided without prejudice, technical modifications and price changes reserved. Reprints, even excerpts, are only permitted with the approval of S+S Regeltechnik GmbH.



For fast & direct ordering, visit www.SplusS.de