

Configuration variants of room operating units

Room temperature sensors and measuring transducers, on-wall, device series Baldur

Housing temperature sensors are electric contact thermometers for measuring temperatures in the gases (air) surrounding them on all sides. Room temperature sensors/measuring transducers are used for measuring air temperature (in non-precipitating air), for changing setpoint values, for presence detection, or as operating panels with push-buttons, switches, potentiometers, status indicators (LEDs) in residential, working, office and business facilities as well as in the industrial sector.

Here are some design and configuration examples of variants of the new Baldur series devices that can be individually customized ...

DEVICE SERIES

Baldur 1 (85 x 85 x 27 mm)

Baldur 2 (98 x 98 x 33 mm)

Baldur lying



Baldur 1 without operating elements



Baldur 1 with display



Baldur 1 with display and potentiometer



Baldur 1 with potentiometer, push-button, and LED



Baldur 1 with potentiometer and rocker switch



Baldur 1 with potentiometer and push-buttons



Baldur 1 with potentiometer and LEDs



Baldur 1 with potentiometer and LEDs



Baldur 1 with potentiometer and LEDs





Baldur 2
without operating elements



Baldur 2
with display



Baldur 2 with display,
potentiometer, and LEDs



Baldur 2
with LEDs and push-buttons



Baldur 2
with LEDs and push-buttons



Baldur 2 with potentiometer,
turn switch, and LEDs



Baldur 2 with potentiometer,
turn switch, and LEDs



Baldur 2 with potentiometer,
push-buttons, LEDs, and rocker switch



Baldur 2 with potentiometer,
turn switch, and LEDs



Baldur 2 with potentiometer
and turn switch



Baldur 2 with potentiometer,
turn switch, LEDs, and push-buttons



Baldur 2 with potentiometer,
turn switch, LEDs, and push-buttons

