



预制分支光缆



产品型号	描述	包装
FL-PDMB3312BG-M010	12C 多模万兆OM3 LC– LC 预制分支光缆 – 10米, LSFRZH	1pcs/pk
FL-PDCB3312BG-M010	12C 多模万兆OM4 LC– LC 预制分支光缆 – 10米, LSFRZH	1pcs/pk
FL-PDSB3312BG-M010	12C 单模OS2 LC– LC 预制分支光缆 – 10米, LSFRZH	1pcs/pk
FL-PDMB3308BG-M010	8C 多模万兆OM3 LC– LC 预制分支光缆 – 10米, LSFRZH	1pcs/pk

预制分支光缆编号规则

A	B	C	D	E	F	G	H	I
Cable Type D Distribution cable	Polarity A key up to key down B key up to key up 备注: 建议采用Type B		Termination End B 1 ST 2 SC 3 LC 4 FC 5 Uniboot LC 6 Uniboot SC		Jacket Type E OFNR F OFNR + end B pulling eye G LSFRZH H LSFRZH + end B pulling eye I OFNR Armored J OFNR Armored + end B pulling eye K LSFRZH Armored L LSFRZH Armored + end B pulling eye S TPU Armored (outdoor) T TPU Armored (outdoor)+ end B pulling eye X OFNP Y OFNP + end B pulling eye		Length 001 -XXX	
Fiber Type B BaseCap 62.5/125 μm OM1 Multimode H HiCap 50/125 μm OM2 Multimode M MaxCap Safe 300 BI-OM3 50/125 μm C MaxCap Safe 550 BI-OM4 50/125 μm T TeraSafe 9/125 μm BI-OS2 / G.657.A1 S TeraSafe Plus 9/125 μm SBI-OS2I / G.657.A2		Termination End A 1 ST 2 SC 3 LC 4 FC 5 Uniboot LC 6 Uniboot SC		Fiber Count 04B 4C Fiber 06B 6C Fiber 08B 8C Fiber 12B 12C Fiber		Unit of Measure F Feet M Meters		