

主干光缆编码规则

FL-PA	B	C	D	E	FFF	G	-	H	III	-	JJ
Cable Type T Trunk cable	Polarity A key up to key down B key up to key up 备注: 建议采用Type-B		Termination End B 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female		Jacket Type E OFNR F OFNR + end B pulling eye G LSFRZH H LSFRZH + end B pulling eye X OFNP Y OFNP + end B pulling eye	Length 001-XXX					
Fiber Type M MaxCap Safe 300 BI-OM3 50/125 μ m C MaxCap Safe 550 BI-OM4 50/125 μ m T TeraSafe 9/125 μ m BI-OS2 / G.657.A1 S TeraSafe Plus 9/125 μ m SBI-OS2 / G.657.A2	Termination End A 1 MPO low loss MM-male 2 MPO low loss MM-female 3 MPO/APC SM-male 4 MPO/APC SM-female 5 MTP low loss MM-male 6 MTP low loss MM-female 7 MTP/APC SM-male 8 MTP/APC SM-female	Fiber Count 081 8C MPO x 1 121 12C MPO x 1 242 12C MPO x 2 * 241 24C MPO x 1 备注: 24芯默认分支2个12芯MPO (24芯MPO需特别标注)	Unit of Measure F Feet M Meters	Sheath Color YL Yellow (OS2) OR Orange (OM2) AQ Aqua (OM3/OM4) default EV Erika Violet (OM4) another option LG Lime Green (OM5)							

