

Professional Speaker System

T-ARRAY SERIES

T-ARRAY SUB218S

T-ARRAY SUB218S sub-woofer is fitted with tailored driver developed with sophisticated technology and repeated adjustment. It employs two 18" LF compression drivers in symmetric installation, producing much lower frequency with penetrating power, which is strong and elastic at the same time. Combined with the T-ARRAY SAT212P line array loudspeaker, it generates a high SPL, clear and delicate sound as well as a controllable range of full frequency response.

FEATURES:

- High-quality components to ensure the speaker's stability and effectiveness.
- Natural bass based on the theory of band-pass
- Low frequency descend degree reaching to 35Hz
- New tridimensional and delicate appearance designed with beveled edge
- Long-time quality guarantee freeing users from worries

APPLICATIONS:

Multifunctional Halls, High-grade Hotels and Clubs, Mobile Performances and Sound Reinforcement for Bands, etc.

SPECIFICATIONS:

FREQUENCY RESPONSE	32Hz - 350Hz
DRIVERS	2×18" (460mm) / 4" voice coil LF
RATED POWER	1200W RMS, 4800W peak
SENSITIVITY	102dB 1watt / 1 metre
MAXIMUM SPL	133dB continuous, 139dB peak
NOMINAL IMPEDANCE	4 ohms
CONNECTORS	2 × Speakon NI4
DIMENSION(WxDxH)	1010mm × 835mm × 550mm
NET WEIGHT	93kg/PC

CONFIGURATION

