ZenithPura

苏州新鼎汇环保科技有限公司

SUZHOU XINDINGHUI ENVIRONMENTAL PROTECTION TECHNOLOGY CO., LTD.

地址：江苏省苏州市相城区元和街道宣公路588号元和塘科技文化研发社区1号楼5楼550室

ADD: Room 550, 5th Floor, Building 1, Yuanhetang Science and Technology Culture R&D Community, No. 588 Xuangong Road, Yuanhe Street, Xiangcheng District, Suzhou City, Jiangsu Province

TEL: +86 13913135613　E-mail：sunny@zenithpura.com　www.zenithpura.com

Airbrush Compressor

TC-80 series

Features:

- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE,GS, ETL, ROHS Approved.



TC-80



TC-801



TC-802



TC-803

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-80	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/4	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-801	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.5	25.5*13.5*17	48*29*52	6	21/24
TC-802	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6
TC-803	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6



TC-802K

Airbrush Compressor

TC-82 series

Features:

- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE, GS, ETL, ROHS Approved.



TC-81



TC-811



TC-812



TC-813

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-82	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/4	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-821	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.5	25.5*13.5*17	48*29*52	6	21/24
TC-822	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6
TC-823	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6



TC-812K

Airbrush Compressor
HANFONG Series

Aluminum handle

TC-82 series

Features:

- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE, GS, ETL, ROHS Approved.



TC-82



TC-821



TC-822



TC-823

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-82	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/4	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-821	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.5	25.5*13.5*17	48*29*52	6	21/24
TC-822	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6
TC-823	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6

Airbrush Compressor
HANFONG Series



TC-88T

Features:

- Piston type, oil free, none air polluted.
- It can start with pressure, continuous working, powerful.
- Air tank, providing smooth air flow, zero pulse.
- Safety protected devices for air tank.
- Air pressure gauge, air filter, pressure adjustable.
- Double air pressure switch:
  Switch 1: low pressure auto stop switch for airbrush purpose
  Switch 2: high pressure none stop switch for high pressure air tools.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- CE, GS, ETL, ROHS Approved.

TC-90

Features:

- Twin cylinder, high air flow, can operate with many airbrushes.
- Piston type, oil free, none air polluted.
- It can start with pressure, continuous working, powerful.
- Air tank, providing smooth air flow, zero pulse.
- Safety protected devices for air tank.
- Air pressure gauge, air filter, pressure adjustable.
- Double air pressure switch:
  Switch 1: low pressure auto stop switch for airbrush purpose
  Switch 2: high pressure none stop switch for high pressure air tools.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- CE, GS,ETL, ROHS Approved.



Twin cylinder airbrush compressor

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Tank	Max. Pressure		Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	L	Bar	Psi	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-88T	0.2-1.0	1/5	1450	1700	4	57	3	43	30-35	3.0	6	86	1/8	5	31*13.5*31	63*33.5*34.5	4	20/23
TC-90	ALL	1/3	1450	1700	4	57	3	43	30-35	--	6	86	1/8	5.5	32*13.5*20.5	67*38.5*26	4	22/25
TC-90T	ALL	1/3	1450	1700	4	57	3	43	30-35	3.5	6	86	1/8	7	32*13.5*31	51*36*35	3	21/24



Twin cylinder airbrush compressor with tank

TC-90T

Features:

- Twin cylinder, high air flow, can operate with many airbrushes.
- Piston type, oil free, none air polluted.
- Air tank, providing smooth air flow, zero pulse.
- Safety protected devices for air tank.
- Air pressure gauge, air filter, pressure adjustable.
- Double air pressure switch:
  Switch 1: low pressure auto stop switch for airbrush purpose
  Switch 2: high pressure none stop switch for high pressure air tools.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Can operate with small air nailer tools,spray gun.
- Low noise, 47db.
- CE, GS,ETL, ROHS Approved

Airbrush Compressor
HANFONG Series


TC-09

TC-09
Features:
- Dual voltage transfer in 115V/230V voltage.
- Oil less, membrane type, none air polluted.
- Big membrane produce air, high air flow.
- Convenient to take, suitable for services and moving work.
- Low noise, about 55db..


TC-09A

TC-09A
Features:
- Dual voltage transfer in 115V/230V voltage.
- Oil less, membrane type, none air polluted.
- Big membrane produce air, high air flow.
- Convenient to take, suitable for services and moving work.
- Low noise, about 55db..

Model	power	Speed/min		Supply Air	Air flow	Max. Pressure		Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (kg)
	HP	50Hz	60Hz	Constructure	L/min	Bar	Psi	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-06	1/4	1450	1700	Membrane	65-68	3.5	50	1/4	4.5	25*12.5*17	44.3*28.6*40.5	6	27/29
TC-09	1/3	1450	1700	Membrane	128-135	3.5	50	1/4	9	37.6*16.5*25.5	38*38*25.5	2	18/20

TC-09K
Features:
- Dual voltage transfer in 115V/230V voltage.
- Oil less, membrane type, none air polluted.
- Big membrane produce air, high air flow.
- Convenient to take, suitable for services and moving work.
- Low noise, about 55db..


TC-09K

Airbrush Compressor
HANFONG Series


TC-100


TC-100K



TC-100K
It's very suitable to be used for airbrush makeup, airbrush nail, spray flowers, cake decorating and etc, because of its non-oil design and continuously work.

Including:
- 1 X 12V DC mini compressor
- 1 x single action airbrush AB-207
- 1 x airbrush holder
- 1 x AC adapter
- 1 x air hose (1.8M)

Specification:
- Air Pressure:25psi
- Air flow: 10L/min
- With 360 degree circumvolve airbrush holder.
- Working pressure adjustable;
- AC adapter
- Input: 100-250V, 50-60 HZ
- Output: 12V DC, 1.6A ,

Note:
It need to cool down after 30 minutes working.

Airbrush Compressor
ROYAL Series

TC-20 series
- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected!
- It will turn off automatically when the motor over heated.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE, GS,ETL, ROHS Approved.



TC-20



TC-20 Black



TC-20A



TC-20B



TC-20C

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-20	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/4	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-20A	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.5	25.5*13.5*17	48*29*52	6	21/24
TC-20B	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6
TC-20C	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6



TC-20BK
- This high-quality airbrushing kit is perfect for commercial arts, illustration,
  photo retouching, temporary tattoos, cake decorating, crafts, hobbies and any \ other airbrushing items.
- Airbrush compressor: TC-20B
- Airbrush: AB-130(optional)
- Air Hose: AH-24
- Holder:AH-303(optional)

Airbrush Compressor
ROYAL Series

Aluminum handle

TC-22 series
- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected!
- It will turn off automatically when the motor over heated.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE,GS, ETL, ROHS Approved.



TC-22



TC-22A



TC-22B



TC-22C

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (Kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-22	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/4	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-22A	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.5	25.5*13.5*17	48*29*52	6	21/24
TC-22B	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6
TC-22C	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6



TC-22BK
- This high-quality airbrushing kit is perfect for commercial arts, illustration, photo retouching, temporary tattoos, cake decorating, crafts, hobbies and any other airbrushing items.
- Airbrush Compressor: TC-22B
- Airbrush: AB-130(optional)
- Air Hose: AH-24
- Holder: AH-303(optional)

Airbrush Compressor
ROYAL Series

TC-20T

Features:
- Piston type, oil free,none air polluted.
- It can start with pressure, continuous working, powerful.
- Air tank, providing smooth air flow, zero pulse.
- Safety protected devices for air tank.
- Air pressure gauge, air filter, pressure adjustable.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Low noise, 47db.
- CE, GS,ETL, ROHS Approved.



TC-20T

With Frame



TC-30F

Twin cylinder airbrush compressor with tank with frame

Features:
- Twin cylinder airbrush compressor with tank with frame.
- High air flow, can operate with many airbrushes.
- Piston type, oil free, none air polluted.
- Air tank, providing smooth air flow, zero pulse.
- Safety protected devices for air tank.
- Air pressure gauge, air filter, pressure adjustable.
- Double air pressure switch:
  Switch 1: low pressure auto stop switch for airbrush purpose
  Switch 2: high pressure none stop switch for high pressure air tools.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Can operate with small air nailer tools,spray gun.
- Low noise, 47db.
- CE, GS,ETL, ROHS Approved

Model	Suitable airbrush	power	Speed/min		Auto stop		Auto start		Air flow	Tank	Max. Pressure		Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight (kg)
	Nozzle	HP	50Hz	60Hz	Bar	Psi	Bar	Psi	L/min	L	Bar	Psi	BSP	Kg	L*W*H(cm)	L*W*H(cm)	Pcs	N.w./G.w.
TC-20T	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	3.0	--	--	1/8	5	31*13.5*31	63*33.5*34.5	4	20/23
TC-30F	ALL	1/3	1450	1700	4	57	3	43	30-35	3.0	6	86	1/8	7.5	34*30*28	61.5*35*29.5	2	15/18
TC-18	0.2-1.0	1/5	1450	1700	4	57	3	43	23-25	--	--	--	1/8	3.6	25.5*13.5*20.5	48*29*52	6	21.6/24.6



TC-18

Features:
- Piston type, oil free
- It can start with pressure, continuous working, powerful.
- Much safer! thermally protected! It will turn off automatically when the motor over heated.
- Air pressure gauge, air filter, pressure adjustable.
- Low noise, 47db.
- Auto stop function.
- Pressure-adjustable.
- CE, GS,ETL, ROHS Approved.

Inflation Air Compressor/Vacuum Pump

Features:
- Oil less, piston type, none air polluted
- Collocated with multi-functional charging air hose suitable for:
  A. charging cars, auto bikes.
  B. Charging bikes.
  C. Charging different kinds of balls.
- Open and closed the tyre valves.
- The gauge can show the charging pressure directly.
- It can start with pressure, powerful performance.
- Low noise, about 47db .



TC-802W
Inflation air compressor



TC-80W
Inflation air compressor

Model	power	Speed/min		Air Producing			Air flow	Max. Pressure		Vacuum Degree	Adapter	N.W.	Single Dim.	Carton Dim.	PCS/CTN	Weight
	HP	50Hz	60Hz	Constructure	Dia	Qty	L/min	Bar	Psi	mmHG	BSP	Kg	L*W*H	L*W*H	Pcs	N.w./g.w.
TC-802W	1/5	1450	1700	Piston	40	1	23-25	4	57	--	AH-25A	3.6	25.5*13.5*17	48*29*52	6	21.6/24.6
TC-80W	1/5	1450	1700	Piston	40	1	23-25	6	86	--	AH-25	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-88	1/5	1450	1700	Piston	40	1	23-25	--	--	600	1/8	3.5	25.5*13.5*17	48*29*52	6	21/23
TC-88W	1/5	1450	1700	Piston	40	1	23-25	6	86	600	1/8	3.4	21.5*13.5*17	48*29*52	6	20.4/23.4
TC-99	1/3	1450	1750	Piston	40	2	30-35	--	--	600	1/8	5.2	30*13.5*20.5	67*38.5*26	4	20.8/23.8



Vacuum pump



Inflation air compressor/ vacuum pump



Twin Cylinder Vacuum pump

TC-88

Features:
- Oil less, piston type, none air polluted
- The gauge can show the vacuum degree when vacuuming.
- Low noise, about 47db

TC-88W

Features:
- Oil less, piston type, none air polluted
- Collocated with multi-functional charging air hose suitable for:
  A. charging cars, auto bikes.
  B. Charging bikes.
  C. Charging different kinds of balls.
- Open and closed the tyre valves.
- The gauge can show the charging pressure directly.
- The customer change the inflation pump into vacuum pump can easily just change the muffle and air outlet.
- Low noise, about 47db .

TC-99

Features:
- Oil less, piston type, none air polluted
- The gauge can show the vacuum degree when vacuuming.
- Low noise, about 47db