

SPECIFICATION

UL Model:	UL2464	Document Number	Made Date	Rev:
Specification:	26AWGx5C	WCH19080603	2019-08-06	1.0V
Cross Section				
Technical Parameters				
Conductor	Specification	(AWG)	26	
	Material		Tinned Stranded Copper	
	Configuration	(mm)	TS30/0.08±0.007	
Insulation	Average Thickness	(mm)	0.23	
	Minimum Thickness	(mm)	0.20	
	Over Diameter	(mm)	1.00±0.10	
	Material		PP (RoHS)	
	Colour		1.Red, 2.Green, 3.Violet, 4.Grey, 5.Black	
Assembly	Screened Shield		No Shield	
	Filler	(mm)	10S/5SOL*1PCS Cotton Rope	
Jacket	Average Thickness	(mm)	0.90	
	Minimum Thickness	(mm)	0.72	
	Over Diameter	(mm)	4.50±0.20	
	Material		PVC (RoHS)	
	Colour		Matte Black	
Electrical Capability	Rated Temperature	(°C)	80	
	Rated Voltage	(V)	300	
	Conductor Resistance	(Ω/KM 20°C)	150	
	Insulation Resistance	(MΩ/KM 20°C)	100	
Marking	As per standard of UL2464			